

CENTRAL HYDRAULICS INC.

•Daytona Beach •Cocoa •Leesburg •Ocala •Tampa 1-800-264-9571

T600AA - Hard Wall Marine Exhaust Hose USCG/SAE J1527 B2

Petroleum



Now In Stock!



APPLICATION

Fuel, oil and hydraulic fluids suction and delivery with up to 50% aromatic content. Suitable for exhaust gas from water cooled stationary or marine diesel engines.

COVER

Black NBR/PVC blend — abrasion, ozone, hydrocarbon and fire resistant.

REINFORCEMENT

High tensile textile cords and 4 highly flexible steel helix wires.

TUBE

Black NBR — exhaust gas, fuel and fire resistant.

BRANDING

ALFAGOMMA – ITALY T600 MARINE EXHAUST/
FUEL S & D – <SIZE> – USCG/SAE J1527 TYPE B2
(in red letters)

TEMPERATURE RANGE

-22°F to 212°F

STANDARD LENGTH

25 or 50 feet

BRANDING

ALFAGOMMA – ITALY T600 MARINE EXHAUST/
FUEL S & D
– <SIZE> – USCG/SAE J1527 TYPE B2 (in red letters)



Kuriyama of America, Inc.

SERIES NO.	Nominal ID	Nominal OD	APPROX. WT. lbs./100 ft.	MAX. REC. WP (PSI)	MIN. BEND RADIUS (in.)
	(in.)	(in.)			
T600AA062	5/8	1.02	36	75	2
T600AA075	3/4	1.18	44	75	2 1/4
T600AA067	7/8	1.26	48	75	2 3/4
T600AA100	1	1.38	54	75	3 1/4
T600AA112	1 1/8	1.50	58	75	3 1/4
T600AA125	1 1/4	1.65	65	75	3 3/4
T600AA137	1 3/8	1.77	69	75	4 1/4
T600AA150	1 1/2	1.89	75	75	4 1/2
T600AA162	1 5/8	2.05	81	75	5
T600AA175	1 3/4	2.16	86	75	5 1/4
T600AA189	1 7/8	2.28	91	75	5 3/4
T600AA200	2	2.40	97	75	6
T600AA225	2 1/4	2.64	108	75	6 3/4
T600AA238	2 3/8	2.76	124	75	7
T600AA250	2 1/2	2.87	130	75	7 1/2
T600AA275	2 3/4	3.11	141	75	8 1/4
T600AA300	3	3.39	152	75	9
T600AA350	3 1/2	3.94	190	75	10 1/2
T600AA400	4	4.41	212	75	12
T600AA450	4 1/2	5.08	270	75	13 1/2
T600AA500	5	5.55	302	75	15

Fax: 386-257-5728 Tele. 1-800-264-9571 sales@centralhydraulics.com www.centralhydraulics.com